



Specialty Paints & Products for
Sign · Branding · Re-Imaging
1.800.421.7961

Q-SOLV™ AR™ SERIES ALCOHOL REDUCERS

Q-SOLV™ AR™ Series Reducers are specifically designed to reduce **Q-COAT TC™** Transparent Coatings to provide the best spray application properties. Temperature, relative humidity, air movement, and application surface size all play a major role to be successful in painting any surface. Selection of the Reducer is the key for best results.

QH&F **Environmentally Friendly** Product.

RECOMMENDED REDUCER APPLICATIONS WITH Q-COAT TC™ TRANSPARENT COATINGS:

Polycarbonate, acrylic, impact modified acrylic, CAB, ABS, styrene, and most flexible vinyl.
Many existing translucent plastic paint finishes. Test plastic compatibility prior to production runs.

Q-SOLV AR™ CONVENTIONAL ALCOHOL REDUCERS:

- | | |
|--|---|
| Q-SOLV™ AR0055™ Alcohol Fast Reducer: | Use below 70°F on small or large surface areas. |
| Q-SOLV™ AR0066™ Alcohol Medium Reducer: | Use between 70°F-85°F on all surface sizes. |
| Q-SOLV™ AR0071™ Alcohol Slow Reducer: | Use above 85°F on all surface sizes. |
| Q-SOLV™ AR0077™ Alcohol Retarder: | Use 5-10% with AR series reducers if needed. |

Always test surface preparation, primer and topcoat compatibility to determine acceptability before any production run.

Disclaimer: Technical information and suggested uses are believed to be reliable by QH&F Ltd., but such information or suggestions do not constitute a warranty. QH&F Ltd. has no control over the conditions under which the product is stored, handled, used or applied. Buyers must determine for themselves the suitability of each product for their specific use.