Specialty Paints & Products for
Sign · Branding · Re-Imaging
1.800.421.7961

Q-SOLV™ SR™ SERIES AIR DRY REDUCERS

Q-SOLV™ SR™ Series Reducers are specifically designed to reduce **Q-COAT AC™** Air Dry Coatings to provide the best application properties. Temperature, relative humidity, air movement, and application surface size all play a major role to be successful in painting any surface. Selection of the Reducer is the key for best results.

QHF **Environmentally Friendly** Product.

For use with Acrylic, ABS, metal, wood, fiberglass and many existing paint finishes.
Always test compatibility prior to production runs.

Q-SOLV SR™ REDUCERS:

Q-SOLV™ SR0060™ Reducer:	Use below 85°F on small or large surface areas.
Q-SOLV™ SR0064™ Retarder:	Use as needed with SR Series Reducers above 85°F.



Reduction Ratio for Brush and Roll:
1 part **Q-COAT AC™** Coating Color
¼ part or as needed **Q-SOLV SR0060™** Reducer
For large surface areas or high temperatures an additional amount 5-10% of **Q-SOLV™ SR0064™** Retarder may be required.

Always test surface preparation, primer and topcoat compatibility to determine acceptability before any production run.

Disclaimer: Technical information and suggested uses are believed to be reliable by QH&F Ltd., but such information or suggestions do not constitute a warranty. QH&F Ltd. has no control over the conditions under which the product is stored, handled, used or applied. Buyers must determine for themselves the suitability of each product for their specific use.

® is a registered trademark and ™ is a trademark of Quill Hair & Ferrule LTD. Copyright © 2009. Quill Hair and Ferrule LTD. All Rights Reserved.