Specialty Paints & Products for
Sign · Branding · Re-Imaging
1.800.421.7961

Q-SOLV™ UR™ SERIES URETHANE REDUCERS

Q-SOLV™ UR™ Series Reducers are specifically designed to reduce **Q-COAT UC™** Urethane Coatings to provide the best spray application properties. Temperature, relative humidity, air movement, and application surface size all play role in painting any surface. Selection of the proper speed reducer is the key for best results.

QHF **Environmentally Friendly** Product.

RECOMMENDED REDUCER APPLICATIONS WITH Q-COAT UC™ URETHANE COATINGS:

Aluminum, Fiberglass, steel and many existing paint finishes. Test compatibility prior to production runs.

Q-SOLV UR™ REDUCERS:

Q-SOLV UR1054™ Fast Reducer:	Use below 75°F on small / large surface areas
Q-SOLV UR1056™ Medium Reducer:	Use above 75°F on small / large surface areas
Q-SOLV UR1060™ Slow Reducer:	Use above 85°F on small / large surface areas
Q-SOLV UR1062™ Extra Slow Reducer:	Use above 85°F on small / large surface areas
Q-SOLV UR1081™ Thickening Additive:	Replaces the reducer when converting to a brush / roll product
Q-SOLV UR1083™ Matting Additive:	Use as a substitute for some or all of the reducer to lower the gloss level
Q-SOLV UR1085™ Odor Mask Additive:	Adds a citrus scent
Q-SOLV UR1091™ Leveling Additive:	Fish-eye remover - use only as needed
Q-SOLV UR1094™ Accelerator:	Accelerator and Pot Life Extender
Q-SOLV UR1099™ Accelerator:	Accelerator
Q-SOLV UR1154™ Low VOC Fast Reducer:	Use below 75°F on small / large surface areas
Q-SOLV UR1156™ Low VOC Med Reducer:	Use above 75°F on small / large surface areas
Q-SOLV UR1160™ Low VOC Slow Reducer:	Use above 85°F on small / large surface areas



Reduction Ratio:
4 parts **Q-COAT UC™** Coating Color
1 part **Q-ACTV™ UA5000™** Activator
1 part **Q-SOLV UR™** Series Reducer

Specialty Paints & Products for
Sign · Branding · Re-Imaging
1.800.421.7961

Q-SOLV™ UR™ SERIES URETHANE REDUCERS

Optional Additives:

Q-SOLV UR1083™ MATTING ADDITIVE:

Use as a substitute for some or all of the reducer to lower the gloss level

Q-SOLV UR1085™ ODOR MASK ADDITIVE:

Up to ½ oz Odor Mask Additive per mixed quart

Q-SOLV UR1091™ LEVELING ADDITIVE:

Up to ½ oz Leveling Additive per mixed quart

Q-SOLV UR1094™ ACCELERATOR:
Q-SOLV UR1099™ ACCELERATOR:

Up to ½ oz Accelerator per mixed quart in high gloss level colors
Up to 1 oz Accelerator per mixed quart in lower gloss level colors

Always test surface preparation, primer and topcoat compatibility to determine acceptability before any production run.

Disclaimer: Technical information and suggested uses are believed to be reliable by QH&F Ltd., but such information or suggestions do not constitute a warranty. QH&F Ltd. has no control over the conditions under which the product is stored, handled, used or applied. Buyers must determine for themselves the suitability of each product for their specific use.

® is a registered trademark and ™ is a trademark of Quill Hair & Ferrule LTD. Copyright © 2009. Quill Hair and Ferrule LTD. All Rights Reserved.